

Concrete Hammers

CH-470



Input	1,050 W
Power	8.8 joules
Hammering Frequency	3,000 min
Shank Type	17 mm Hex
Overall Dimensions	445 x 106 x 231 mm
Weight	5.2 kg

- * Professional concrete hammer.
- * Built-in handle and barrel shock absorber decreases the vibration.
- * Quick retainer enables the bull point to be easily changed.
- * Automatic cut off brush for longer tool life.
- * Grease packed lubrication provides long operation without special maintenance.
- * Durable aluminium die cast components are used in major parts.

CH-470R



Input	1,050 W
Power	8.8 joules
Hammering Frequency	3,000 min
Shank Type	19 mm Hex (EUR Shank)
Overall Dimensions	445 x 106 x 231 mm
Weight	5.2 kg

- * 19 mm Hex European type shank version of CH-470.

CH-485



Input	1,130 W
Power	15 joules
Hammering Frequency	1,800 min
Shank Type	21 mm Hex (STD /EUR Shank)
Overall Dimensions	509 x 102 x 254 mm
Weight	8.5 kg

- * 21 mm hex shank model with high power motor.
- * Standard or European shank model is also available.
- * Automatic cut-off brush for longer tool life.
- * Grease packed lubrication provides long operation without special maintenance.
- * Durable aluminium die cast components are used in major parts.



Specifications

Model	Input	Power	Hammering Frequency	Shank Type	Overall Dimensions	Weight
CH-470	1,050 W	8.8 joules	3,000 min	17 mm Hex	445 x 106 x 231 mm	5.2 kg
CH-470R	1,050 W	8.8 joules	3,000 min	19 mm Hex (EUR Shank)	445 x 106 x 231 mm	5.2 kg
CH-485	1,130 W	15 joules	1,800 min	21 mm Hex (STD / EUR Shank)	509 x 102 x 254 mm	8.5 kg

Concrete Hammers

CH-500N



Input	1,350 W
Power	42 joules
Hammering Frequency	1,200 min
Shank Type	30 mm Hex
Overall Length	728 mm
Weight	17.0 kg

- * 30 mm hex shank model for professional heavy duty use.
- * Automatic cut-off brush for longer tool life.
- * Grease packed lubrication provides long operation without special maintenance.

CH-500P



Input	1,250 W
Power	42 joules
Hammering Frequency	1,300 min
Shank Type	30 mm Hex
Overall Length	728 mm
Weight	16.7 kg

- * Double Insulation model of CH-500N.



Specifications

Model	Input	Power	Hammering Frequency	Shank Type	Overall Length	Weight
CH-500N	1,350 W	42 joules	1,200 min	30 mm Hex	728 mm	17.0 kg
CH-500P	1,250 W	42 joules	1,300 min	30 mm Hex	728 mm	16.7 kg